

# ZOTAC GAMING GeForce RTX 5090 ARCTICSTORM AIO

#### SKU: ZT-B50900K-30P | EAN: 8886307701541 | UPC: 810012085953

The ZOTAC GAMING GeForce RTX 5090 ARCTICSTORM AIO is the first high-end graphics card by ZOTAC GAMING to utilize a full-sized 360mm Liquid Cooling AIO and full-coverage copper cold plate for the ultimate cooling performance. Designed for gaming enthusiasts who want pure speed and exceptional temperatures, the ARCTICSTORM AIO redefines high-end graphics.















# **KEY FEATURES**

- NVIDIA Blackwell Architecture
- 5th Generation Tensor cores
- 4th Generation RT cores
- NVIDIA DLSS 4
- Game Ready and NVIDIA Studio Drivers
- NVIDIA® GeForce Experience™
- NVIDIA Broadcast, NVIDIA G-SYNC®

- 32GB GDDR7 graphics memory
- Superior Liquid Cooling, up to 30% cooler than air-cooled variant
- 360mm AIO Liquid Cooler
- Full coverage copper cooling plate
- Large Infinity Mirror Design
- Triple 120mm Fans deliver up to 50% quieter performance
- Metal backplate
- 4-Zone SPECTRA 2.0 ARGB lighting
- ZOTAC GAMING FireStorm Utility









#### **TECHNICAL SPECIFICATIONS**

#### **SPECIFICATIONS**

- NVIDIA GeForce RTX 5090 GPU
- 21760 CUDA cores
- 32GB GDDR7 memory
- 512-bit memory bus
- Engine boost clock: 2437 MHz
- Memory clock: 28 Gbps
- PCI Express 5.0 x16

#### SOFTWARE COMPATIBILITY

- Game Ready and NVIDIA Studio Drivers
- PCI Express® Gen 5
- Microsoft DirectX® 12 Ultimate
- Vulkan RT APIs, Vulkan 1.4
- OpenGL 4.6
- Windows 11 / Windows 10 64-bit (v1809
   November 2018 or later)

### **CONNECTIONS**

- 3 x DisplayPort 2.1b with UHBR20 (up to 4K 480Hz or 8K 165Hz with DSC)
- 1 x HDMI® Connector

  (Supports 4K 480Hz HDR or 8K 120Hz HDR with DSC, and Gaming VRR as specified in the HDMI 2.1b Specification)
- HDCP 2.3 support
- Up to 4 displays simultaneously

#### POWER REQUIREMENTS

- 1000-watt power supply recommended
- 575-watt max power consumption
- 1 x 12v-2x6 power input\*

#### INSIDE THE BOX

- ZOTAC GAMING GeForce RTX
   5090 ArcticStorm AIO
- User Manual
- 4 x 8-pin-to-16-pin cable
- ARGB GPU Support Bracket

#### **DIMENSIONS**

## Card:

- Length: 251.6 mm (9.9 in)
- Height: 160.1 mm (6.3 in)
- Width: 2.5 slot (49 mm) (1.9 in)
   Tube Length: 520mm (20.47 in)

#### Radiator (with fans):

- Length: 394 mm (15.5 in)
- Height: 55.7 mm (2.2 in)
- Width: 122.8 mm (4.8 in)

#### Radiator (without fans):

- Length: 394 mm (15.5 in)
- Height: 27.2 mm (1.07 in)
- Width: 119.2 mm (4.7 in)

#### Box:

- Height: 562mm (22.1 in)
- Width: 438mm (17.2 in)
- Depth: 172mm (6.8 in)

©2025 ZOTAC Technology Pte. Ltd. All rights reserved. All company and/or product names may be trade names, trademarks and/or registered trademarks of the respective owners with which they are associated. Features, pricing, availability and specifications are subject to change without notice. ZOTAC Technology Limited does not warrant the accuracy, completeness or reliability of information, materials and other items contained on this website or server. No liability is assumed with respect to the use of the information contained herein. When accessing this website, users acknowledge that ZOTAC Technology Limited will not be liable in any event for any damages arising out of the use of this site or

©2025 NVIDIA Corporation. NVIDIA, the NVIDIA logo, and GeForce are registered trademarks of NVIDIA Corporation in the U.S. and other countries. All rights reserved.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

\*High power consumption, please carefully read your PSU manual

For more information please visit:

**ZOTAC.COM** 

any websites linked to it.