



CI329 nano

SKU: ZP-CI329NANO













TECHNICAL SPECIFICATIONS

- FEATURES

 Intel Celeron N4100 Quad core
 System-on-Chip with 4MB cache
 HDMI, DisplayPort, VGA display output
 Dual Gigabit Ethernet port
 RS-232 serial port for legacy connectivity
 Hardware watchdog timer
 Rugged passive cooling aluminum enclosure

- PROCESSOR
 Intel Celeron N4100, Quad-core 1.1GHz/2.4GHz
 4MB L2 cache

- GRAPHICS ENGINE

 Integrated Intel UHD Graphics 600

 HDMI 2.0: 4096x2160 @ 60Hz

 DisplayPort 1.2: 4096x2160 @ 60Hz

 VGA: 1920x1200 @ 60Hz

MEMORY
• 2 x DDR4-2400 SODIMM slots (up to 8GB)

- STORAGE

 1 x SATA-III 2.5" HDD/SSD bay

 1 x M.2 2242/2260 key-M socket for SATA SSD

 SD/SDHC/SDXC flash memory card slot

DISPLAY OUTPUT • 1 x HDMI 2.0 • 1 x DisplayPort 1.2 • 1 x VGA

- AUDIO INTERFACE

 8-channel digital audio via HDMI port
 3.5mm stereo headphone jack
 3.5mm microphone jack

- NETWORKING
 2 x Gigabit Ethernet port
 IEEE 802.11ac/a/b/g/n WIFI

POWER INPUT • DC 19V, 40W

OPERATING TEMPERATURE

- SUPPORTED OS
 Microsoft Windows
 Ubuntu 16.04 LTS

- ZBOX PRO CI329 nano
 Universal AC adapter
 Power Cord
 (bundled cable type dependent on region)
 VESA mount kit
 L-mount kit
 Wi-Fi antenna
 USB flash with software & user's manual





























FANLESS USB 3.0
OPERATION SUPERSPEED

RS-232

WATCHDOG