



CI330 nano

SKU: ZP-CI330NANO















TECHNICAL SPECIFICATIONS

- FEATURES Intel Celeron N3160 Quad core System-on-Chip with 2MB cache Dual HDMI, VGA display output Display Continuity switch for digital signage application HDMI connector with screw locking DC jack with screw locking Hardware watchdog timer Rugged passive cooling aluminum enclosure

- PROCESSOR
 Intel Celeron N3160 Quad-core 1.6GHz/2.24GHz
 2MB L2 cache

.....

GIGABIT LAN

GRAPHICS ENGINE • Integrated Intel HD Graphics 400 • HDMI 1.4: 3840 x 2160@30Hz, 2560 x 1600@60Hz • VGA: 1920 x 1200@60Hz

802.11 AC

MEMORY • 2 x DDR3L-1600 SO-DIMM slot (Up to 8GB)

FANLESS OPERATION

- DISPLAY OUTPUT 2 x HDMI 1.4 with locking screw 1 x VGA

- AUDIO INTERFACE 8-channel digital audio via HDMI port 3.5mm stereo headphone jack 3.5mm microphone jack

NETWORKING • 1 x Gigabit Ethernet port • IEEE 802.11ac/a/b/g/n WIFI

POWER INPUT • DC 19V, 45W with locking screw

PHYSICAL DIMENSIONS • Length: 160.0mm (6.30in) • Width: 126.7mm (4.99in) • Height: 50.7mm (2in)

- SUPPORTED OS Microsoft Windows Ubuntu 16.04 LTS

- INSIDE THE BOX ZBOX PRO CI330 nano Universal AC adapter Power Cord (bundled cable type dependent on region) VESA mount kit L-mount kit Wi-Fi antenna USB flash with software & user's manual





(IIII

