

Powerful, fast and durable, the ZBOX PRO QTG7A4500 has all it needs to bring speeding performance and powerful professional graphics to the table. Featuring an Intel 8-core 16-thread processor, the professional grade NVIDIA RTX Ampere architecture delivers life-like graphics, and a vast array of connectivity options including USB 3.1 ports, 2.5G Ethernet and WiFi 6E.

With two HDMI 2.1 ports and two DisplayPort 1.4a, it supports up to 4 simultaneous 4K displays to deliver fluid viewing for life-like motion, making it the ideal solution for applications such as scientific visualization, medical analytics, VR & content creation/production, digital signage and much more.



TECHNICAL SPECIFICATIONS

FEATURES

- Intel Core i7 processor (8 cores and 16 threads)
- Quad Display Output powered by NVIDIA RTX graphics
- Hardware watchdog timer: Timeout value = 1-255 (min/sec)
- Active Cooling Embedded Solution
- Durable Full Metal Enclosure
- Long Product Life Cycle

PROCESSOR

- Intel Core i7-11850HE (embedded option) (8-core 2.6GHz up to 4.7GHz)
- 24MB cache, 45W TDP

GRAPHICS ENGINE

- NVIDIA RTX A4500 embedded GPU w/ 256-bit 16GB GDDR6
- NVIDIA Ampere architecture
- 5888 CUDA cores, 184 Tensor Cores, 125W TGP
- HDMI 2.1: up to 4096x2160@60Hz
- DisplayPort 1.4a: up to 4096x2160@60Hz

MEMORY

- 2 x DDR4-3200MHz SO-DIMM slots (up to 64GB)

STORAGE

- 1 x 2.5-inch SATA 3.0 HDD/SSD bay
- 1 x M.2 2242/2260/2280 key-M socket for NVMe/SATA/Optane SSD
- 1 x M.2 2242/2260/2280 key-M socket for NVMe/PCIe 4.0 SSD
- SD/SDHC/SDXC memory card slot

DISPLAY OUTPUT

- 2 x HDMI® Connector (supports 4K 120Hz HDR, 8K 60Hz required dual head with DSC, and Variable Refresh Rate as specified in the HDMI 2.1 Specification)
- 2 x DisplayPort 1.4a

AUDIO INTERFACE

- 8-channel digital audio via HDMI port
- 3.5mm stereo headphone jack
- 3.5mm microphone jack

NETWORKING

- 1 x 2.5Gbit Ethernet, 1 x Gigabit Ethernet port
- WiFi 6E IEEE 802.11ax/ac/a/b/g/n
- Bluetooth 5.2

POWER INPUT

- DC 19.5V, 330W

CONNECTIVITY

- 1 x USB 3.1 Type-C
- 5 x USB 3.1 Type-A
- 1 x Legacy RS232 (COM) port

OPERATING TEMPERATURE

- Main unit: -20°C - +40°C
- AC adapter: +0°C - +40°C

PHYSICAL DIMENSIONS

- Length: 227.0mm (8.94in)
- Width: 202.5mm (7.97in)
- Height: 62.5mm (2.46in)

SUPPORTED OS

- Windows 11 / 10 / 10 IoT ENT LTSC
- Ubuntu 20.04.3 LTS Linux

INSIDE THE BOX

- ZBOX PRO QTG7A4500
- Universal AC adapter
- Power Cord (bundled cable type dependent on region)
- VESA & L-shaped Mounting Kit
- 2 x Wi-Fi Tri-band antenna
- USB Flash Drive with Drivers & User's Manual



WiFi 6E



DUAL LAN



ULTRA HD



SDXC CARD READER



USB 3.1 SUPERSPEED+



RS-232



WATCHDOG TIMER

